

**Description**

Fastener Length: 1-1/8", Thread: 3/8-24, Thread Length: 19/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1581F6T9
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-443-7543
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N NAS1581F6T9 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.594 Inches Nominal
<b>Fastener Length:</b>	1.156 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.5149 Inches Nominal
<b>Head Height:</b>	0.081 Inches Nominal
<b>Grip Diameter:</b>	0.3735 Inches Minimum And 0.3745 Inches Maximum
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	0.562 Inches Nominal
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	16000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>iii Part Name Assigned By Controlling Agency:</b>	Navy Special Project
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581F6T9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.