

Description

Fastener Length: 9/16", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS1581K3H3 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-597-4548 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS1581K3H3 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.363 Inches Nominal |
| Fastener Length: | 0.538 Inches Minimum And 0.568 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.257 Inches Nominal |
| Grip Diameter: | 0.188 Inches Nominal |
| Internal Drive Style: | Recessed Type I |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.190 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams 4928 National Std/spec Single Material Response Or Ams 4967 National Std/spec Single Material Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581K3H3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.