

Description

Fastener Length: 9/16", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1581K3H3
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-597-4548
Schedule B:	8108.90.3060
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS1581K3H3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.363 Inches Nominal
Fastener Length:	0.538 Inches Minimum And 0.568 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.257 Inches Nominal
Grip Diameter:	0.188 Inches Nominal
Internal Drive Style:	Recessed Type I
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.190 Inches Nominal
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 National Std/spec Single Material Response Or Ams 4967 National Std/spec Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581K3H3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.