

**Description**

Fastener Length: 9/16", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1581K3H3
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-597-4548
Schedule B:	8108.90.3060
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS1581K3H3 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.363 Inches Nominal
<b>Fastener Length:</b>	0.538 Inches Minimum And 0.568 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.257 Inches Nominal
<b>Grip Diameter:</b>	0.188 Inches Nominal
<b>Internal Drive Style:</b>	Recessed Type I
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.190 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams 4928 National Std/spec Single Material Response Or Ams 4967 National Std/spec Single Material Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581K3H3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.