

Description

Fastener Length: 1/2", Thread: 10-32, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1581K3R2
Minimum Qty (MOQ):	10
NSN:	5305-01-470-0850
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



NAS1581K3R2



P/N NAS1581K3R2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.337 Inches Minimum And 0.387 Inches Maximum
Fastener Length:	0.471 Inches Minimum And 0.502 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.258 Inches Minimum And 0.305 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Special Features:	Internal Drive Ribbed
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1581 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581K3R2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.