

**Description**

Fastener Length: 11/16", Thread: 10-32, Thread Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1581K3R5                               |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5305-01-184-3757                          |
| Schedule B:             | 8108.90.3060                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NAS1581K3R5



## P/N NAS1581K3R5 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.338 Inches Minimum And 0.388 Inches Maximum             |
| <b>Fastener Length:</b>                      | 0.660 Inches Minimum And 0.690 Inches Maximum             |
| <b>Head Style:</b>                           | Flat Countersunk  |
| <b>Head Diameter:</b>                        | 0.2578 Inches Minimum And 0.3047 Inches Maximum           |
| <b>Grip Diameter:</b>                        | 0.1890 Inches Minimum And 0.1895 Inches Maximum           |
| <b>Internal Drive Style:</b>                 | Offset Cruciform (torque Set)                             |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches  |
| <b>Grip Length:</b>                          | 0.302 Inches Minimum And 0.322 Inches Maximum             |
| <b>Thread Quantity Per Inch:</b>             | 32  |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                             |
| <b>Countersink Angle:</b>                    | 99.0 Degrees Minimum And 101.0 Degrees Maximum            |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip                                     |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads                                  |
| <b>Material:</b>                             | Titanium Alloy Overall                                    |
| <b>Material Document And Classification:</b> | Ams 4967 6al-4v Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf  |
| <b>Specification/standard Data:</b>          | 80205-1581 Professional/Industrial Association Standard   |

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581K3R5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.