

Description

Fastener Length: 1-3/4", Thread: 10-32, Thread Length: 23/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1581K3T22
Minimum Qty (MOQ):	1
NSN:	5305-01-467-1398
Schedule B:	8108.90.3060
ECCN:	EAR99



P/N NAS1581K3T22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.363 Inches Nominal
Fastener Length:	1.723 Inches Minimum And 1.753 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.2578 Inches Nominal
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
End Item Identification:	2320-01-123-1610
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.723 Inches Minimum And 1.753 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Point Shall Be Flat And Chamfered; Name On Standard Is Bolt, 100 Degrees Flush Reduced Head
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Ams4928 Assn Std 1st Material Response Overall Or Ams4967 Assn Std 2nd Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581K3T22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.