

Description

Fastener Length: 21/32", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1581K4T4
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-334-0524
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N NAS1581K4T4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.403 Inches Nominal
Fastener Length:	0.638 Inches Minimum And 0.668 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.3504 Inches Minimum And 0.3988 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1581 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581K4T4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.