

Description

Fastener Length: 1-5/32", Thread: 1/4-28, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | NAS1581V4R12 |
| Minimum Qty (MOQ): | 40 EA |
| NSN: | 5305-01-174-2897 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

P/N NAS1581V4R12 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.332 Inches Minimum And 0.403 Inches Maximum |
| Fastener Length: | 1.143 Inches Minimum And 1.163 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.350 Inches Minimum And 0.399 Inches Maximum |
| Grip Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Special Features: | Internal Drive Ribbed |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams 4967 Comp 6al-4v Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1581 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581V4R12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.