

Description

NAS1587-10C Recessed Washer

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS158710C
Minimum Qty (MOQ):	25
NSN:	5310-00-283-7453
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1587-10C Specifications

Hole Diameter:	0.631 Inches Minimum And 0.643 Inches Maximum
Outside Diameter:	1.062 Inches Nominal
Recess Diameter:	0.765 Inches Minimum And 0.785 Inches Maximum
Material Thickness:	0.078 Inches Nominal
Recess Angle:	90.0 Degrees Nominal
Surface Finish:	63.0 Microinches Bottom
Surface Finish:	63.0 Microinches Top
Material:	Steel Comp 321 Overall Or Steel Comp 347 Overall
Material Document And Classification:	Ams 5510 Assn Std 1st Material Response Overall Or Ams 5512 Assn Std 2nd Material Response Overall Or Qq-s-763 Fed Spec All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed
Style Designator:	Recessed
Specification/standard Data:	80205-nas1587 Professional/industrial Association Standard

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/NAS1587-10C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.