

Description

Hole Diameter: 3/4", Diameter: 1-1/4",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS158712
Minimum Qty (MOQ):	25
NSN:	5310-00-526-1583
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N NAS1587-12 Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.757 Inches Minimum And 0.770 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.062 Inches Nominal
Overall Diameter:	1.250 Inches Nominal
Minimum Tensile Strength:	75000 Pounds Per Square Inch
Surface Finish:	63.0 Microinches Bottom
Surface Finish:	63.0 Microinches Top
Material:	Steel Comp 321 Overall Or Steel Comp 347 Overall
Material Document And Classification:	Mil-s-6721 Mil Spec All Material Responses Overall Or Qq-s-763,cond A Fed Spec All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1587 Professional/Industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1587-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.