

**Description**

size: #10, countersunk, corrosion resistant steel, NAS1587 series recessed washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS15873C
Minimum Qty (MOQ):	100
NSN:	5310-01-030-4916
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



## P/N NAS1587-3C Specifications

<b>Hole Diameter:</b>	0.192 Inches Minimum And 0.198 Inches Maximum
<b>Outside Diameter:</b>	0.459 Inches Minimum And 0.479 Inches Maximum
<b>Recess Diameter:</b>	0.275 Inches Minimum And 0.285 Inches Maximum
<b>Material Thickness:</b>	0.052 Inches Minimum And 0.072 Inches Maximum
<b>End Item Identification:</b>	A-10 Aircraft
<b>Recess Angle:</b>	45.0 Degrees Nominal
<b>Special Features:</b>	Temperature Rated 1200 Degrees Fahrenheit
<b>Material:</b>	Steel Comp 321 Overall And Steel Comp 347 Overall
<b>Material Document And Classification:</b>	Qq-s-763 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-s-5002 Mil Spec Single Treatment Response Overall
<b>Style Designator:</b>	15 Recessed
<b>Specification/standard Data:</b>	80205-nas1587 Professional/Industrial Association Standard

## How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/NAS1587-3C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.