

Description

size: #10, countersunk, corrosion resistant steel, NAS1587 series recessed washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS15873C
Minimum Qty (MOQ):	100
NSN:	5310-01-030-4916
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N NAS1587-3C Specifications

Hole Diameter:	0.192 Inches Minimum And 0.198 Inches Maximum
Outside Diameter:	0.459 Inches Minimum And 0.479 Inches Maximum
Recess Diameter:	0.275 Inches Minimum And 0.285 Inches Maximum
Material Thickness:	0.052 Inches Minimum And 0.072 Inches Maximum
End Item Identification:	A-10 Aircraft
Recess Angle:	45.0 Degrees Nominal
Special Features:	Temperature Rated 1200 Degrees Fahrenheit
Material:	Steel Comp 321 Overall And Steel Comp 347 Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Style Designator:	15 Recessed
Specification/standard Data:	80205-nas1587 Professional/industrial Association Standard

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/NAS1587-3C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.