

P/N NAS1587-5C

Military-Fasteners.com

Description

size: 5/16", countersunk, corrosion resistant steel, NAS1587 series washer

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS15875C
Minimum Qty (MOQ):	50
NSN:	5310-00-476-7366
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N NAS1587-5C Specifications

Hole Diameter:	0.315 Inches Minimum And 0.324 Inches Maximum
Outside Diameter:	0.593 Inches Nominal
Recess Diameter:	0.396 Inches Minimum And 0.406 Inches Maximum
Material Thickness:	0.078 Inches Nominal
Recess Angle:	90.0 Degrees Nominal
Surface Finish:	63.0 Microinches Bottom
Surface Finish:	63.0 Microinches Top
Material:	Steel Comp 321 Overall Or Steel Comp 347 Overall Or Steel Comp 348 Overall
Material Document And	Qq-s-763 Fed Spec 1st Material Response Overall Or Qq-s-763 Fed Spec 2nd Material Response Overall Or Mil-s-6721 Mil Spec All
Classification:	Material Responses Overall
Surface Treatment:	Passivate Overall
Style Designator:	15 Recessed
Style Designator:	Recessed
Specification/standard Data:	80205-nas1587 Professional/industrial Association Standard

How to Order

Order this recessed washer from our inventory online by visiting <u>https://military-fasteners.com/washers/recessed+washers/NAS1587-5C</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.