

Description

size: 5/16", countersunk, corrosion resistant steel, NAS1587 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS15875C |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5310-00-476-7366 |
| Schedule B: | 7318.22.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



* See page 2 for technical characteristics

P/N NAS1587-5C Specifications

| | |
|--|--|
| Hole Diameter: | 0.315 Inches Minimum And 0.324 Inches Maximum |
| Outside Diameter: | 0.593 Inches Nominal |
| Recess Diameter: | 0.396 Inches Minimum And 0.406 Inches Maximum |
| Material Thickness: | 0.078 Inches Nominal |
| Recess Angle: | 90.0 Degrees Nominal |
| Surface Finish: | 63.0 Microinches Bottom |
| Surface Finish: | 63.0 Microinches Top |
| Material: | Steel Comp 321 Overall Or Steel Comp 347 Overall Or Steel Comp 348 Overall |
| Material Document And Classification: | Qq-s-763 Fed Spec 1st Material Response Overall Or Qq-s-763 Fed Spec 2nd Material Response Overall Or Mil-s-6721 Mil Spec All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Style Designator: | 15 Recessed |
| Style Designator: | Recessed |
| Specification/standard Data: | 80205-nas1587 Professional/industrial Association Standard |

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/NAS1587-5C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.