

**Description**

size: 7/16", countersunk, corrosion resistant steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS15877C
Minimum Qty (MOQ):	25
NSN:	5310-00-279-9083
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



## P/N NAS1587-7C Specifications

<b>Hole Diameter:</b>	0.441 Inches Minimum And 0.451 Inches Maximum
<b>Outside Diameter:</b>	0.781 Inches Nominal
<b>Recess Diameter:</b>	0.543 Inches Minimum And 0.557 Inches Maximum
<b>Material Thickness:</b>	0.078 Inches Nominal
<b>Recess Angle:</b>	90.0 Degrees Nominal
<b>Surface Finish:</b>	63.0 Microinches Bottom
<b>Surface Finish:</b>	63.0 Microinches Top
<b>Material:</b>	Steel Comp 321 Overall Or Steel Comp 347 Overall
<b>Material Document And Classification:</b>	Mil-s-6721 Mil Spec All Material Responses Overall Or Qq-s-763 Fed Spec All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	15 Recessed
<b>Style Designator:</b>	Recessed
<b>Specification/standard Data:</b>	80205-nas1587 Professional/industrial Association Standard

## How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/NAS1587-7C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.