

P/N NAS1587-7C

Description

size: 7/16", countersunk, corrosion resistant steel

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS15877C

Minimum Qty (MOQ): 25

NSN: 5310-00-279-9083

ECCN: EAR99

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,









^{*} See page 2 for technical characteristics

P/N NAS1587-7C Specifications

Hole Diameter:	0.441 Inches Minimum And 0.451 Inches Maximum
Outside Diameter:	0.781 Inches Nominal
Recess Diameter:	0.543 Inches Minimum And 0.557 Inches Maximum
Material Thickness:	0.078 Inches Nominal
Recess Angle:	90.0 Degrees Nominal
Surface Finish:	63.0 Microinches Bottom
Surface Finish:	63.0 Microinches Top
Material:	Steel Comp 321 Overall Or Steel Comp 347 Overall
Material Document And Classification:	Mil-s-6721 Mil Spec All Material Responses Overall Or Qq-s-763 Fed Spec All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed
Style Designator:	Recessed
Specification/standard Data:	80205-nas1587 Professional/industrial Association Standard

How to Order

Order this recessed washer from our inventory online by visiting https://military-fasteners.com/washers/recessed+washers/NAS1587-7C and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/recessed+washers/NAS1587-7C and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/recessed+washers/NAS1587-7C and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/washers/nashe