

Description

size: 7/16", countersunk, corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS15877C |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5310-00-279-9083 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



P/N NAS1587-7C Specifications

| | |
|---|--|
| Hole Diameter: | 0.441 Inches Minimum And 0.451 Inches Maximum |
| Outside Diameter: | 0.781 Inches Nominal |
| Recess Diameter: | 0.543 Inches Minimum And 0.557 Inches Maximum |
| Material Thickness: | 0.078 Inches Nominal |
| Recess Angle: | 90.0 Degrees Nominal |
| Surface Finish: | 63.0 Microinches Bottom |
| Surface Finish: | 63.0 Microinches Top |
| Material: | Steel Comp 321 Overall Or Steel Comp 347 Overall |
| Material Document And Classification: | Mil-s-6721 Mil Spec All Material Responses Overall Or Qq-s-763 Fed Spec All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Style Designator: | 15 Recessed |
| Style Designator: | Recessed |
| Specification/standard Data: | 80205-nas1587 Professional/industrial Association Standard |

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/NAS1587-7C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.