

P/N NAS1587-8C

Description

Size: 1/2", countersunk, stainless steel, NAS1587 series washer

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS15878C
Minimum Qty (MOQ):	50
NSN:	5310-00-281-6347
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



^{*} See page 2 for technical characteristics

P/N NAS1587-8C Specifications

Hole Diameter:	0.504 Inches Minimum And 0.515 Inches Maximum
Outside Diameter:	0.875 Inches Nominal
Recess Diameter:	0.604 Inches Minimum And 0.620 Inches Maximum
Material Thickness:	0.078 Inches Nominal
Recess Angle:	90.0 Degrees Nominal
Surface Finish:	63.0 Microinches Bottom
Surface Finish:	63.0 Microinches Top
Material:	Steel Comp 321 Overall Or Steel Comp 347 Overall
Material Document And Classification:	Mil-s-6721 Mil Spec All Material Responses Overall Or Qq-s-763 Fed Spec All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed
Style Designator:	Recessed
Specification/standard Data:	80205-nas1587 Professional/industrial Association Standard

How to Order

Order this recessed washer from our inventory online by visiting https://military-fasteners.com/washers/recessed+washers/NAS1587-8C and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.