

Description

Fastener Length: 1-19/64", Thread: 3/8-24, Thread Length: 43/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS160610
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-850-3530
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1606-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.532 Inches Minimum And 0.682 Inches Maximum
Fastener Length:	1.250 Inches Minimum And 1.297 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.755 Inches Minimum And 0.760 Inches Maximum
Shoulder Diameter:	0.405 Inches Minimum First Shoulder And 0.406 Inches Maximum First Shoulder
Shoulder Length:	0.466 Inches Minimum First Shoulder And 0.488 Inches Maximum First Shoulder
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	100.0 Degrees Nominal
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1606-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.