

## P/N NAS1611-018A

## **Description**

diameter: 0.739", preformed packing, ethylene propylene, phosphate ester resistant

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS1611018A
Minimum Qty (MOQ):	10
NSN:	5331-00-953-1885
Schedule B:	4016.99.6050
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1611-018A Specifications

Outside Diameter:	0.864 Inches Minimum And 0.894 Inches Maximum
Temp Rating:	-70.0 Deg Fahrenheit And 250.0 Deg Fahrenheit
Cross-sectional Height:	0.067 Inches Minimum And 0.073 Inches Maximum
Center Hole Diameter:	0.730 Inches Minimum And 0.748 Inches Maximum
Hardness Rating:	80.0 Shore Durometer A Nominal
Material:	Rubber Ethylene-propylene Class Epm

### **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/o\_rings/NAS1611-018A">https://military-fasteners.com/o\_rings/o\_rings/NAS1611-018A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/NAS1611-018A">https://military-fasteners.com/o\_rings/o\_rings/NAS1611-018A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/NAS1611-018A">https://military-fasteners.com/o\_rings/O\_rings/NAS1611-018A</a> and selecting the quantity you want then click "add to cart".