

**Description**

diameter: 1.364", preformed packing o-ring - ethylene propylene, phosphate ester resistant

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1611028A
Minimum Qty (MOQ):	10
NSN:	5331-01-127-7611
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N NAS1611-028A Specifications

<b>Outside Diameter:</b>	1.485 Inches Minimum And 1.523 Inches Maximum
<b>Temp Rating:</b>	-65.0 Deg Fahrenheit And 160.0 Deg Fahrenheit
<b>Cross-sectional Height:</b>	0.067 Inches Minimum And 0.073 Inches Maximum
<b>Center Hole Diameter:</b>	1.351 Inches Minimum And 1.377 Inches Maximum
<b>Hardness Rating:</b>	80.0 Shore Durometer A Nominal
<b>Material:</b>	Rubber Ethylene-propylene Class Epm
<b>Material Document And Classification:</b>	Nas 1613 Assn Std Single Material Response
<b>Specification/standard Data:</b>	80205-nas1611 Professional/industrial Association Standard

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/NAS1611-028A](https://military-fasteners.com/o_rings/o_rings/NAS1611-028A) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.