

Description

tubing diameter: 3/4", preformed packing, straight tube, ethylene propylene, phosphate ester resistant, NAS1612 series oring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | NAS161212A |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5331-01-287-4828 |
| Schedule B: | 4016.93.5010 |
| ECCN: | EAR99 |
| National Motor Freight: | 148520, Packing Rubr / Gum Compound O / T Foam |



P/N NAS1612-12A Specifications

| | |
|--|---|
| Temp Rating: | -65.0 Deg Fahrenheit And 160.0 Deg Fahrenheit |
| Cross-sectional Height: | 0.116 Inches Nominal |
| Center Hole Diameter: | 0.924 Inches Nominal |
| Hardness Rating: | 88.0 Shore Durometer D Nominal |
| Criticality Code Justification: | Zzzy |
| Special Features: | Green Stripe |
| Material: | Rubber Ethylene-propylene Class Epm |
| Material Document And Classification: | Nas 1613 Assn Std Single Material Response |
| Reference Number Differentiating Characteristics: | Clean law Mil-i-52211 |

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/NAS1612-12A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.