

Description

tubing diameter: 5/16", preformed packing o-ring, straight thread tube fitting boss ethylene propylene, phosphate ester resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS16125 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5331-00-086-2461 |
| ECCN: | EAR99 |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |



* See page 2 for technical characteristics

P/N NAS1612-5 Specifications

| | |
|--|--|
| Temp Rating: | -65.0 Deg Fahrenheit And 250.0 Deg Fahrenheit |
| Cross-sectional Height: | 0.069 Inches Minimum And 0.075 Inches Maximum |
| Center Hole Diameter: | 0.408 Inches Minimum And 0.419 Inches Maximum |
| Special Features: | Rubber O-ring |
| Material: | Rubber Synthetic |
| Material Document And Classification: | Has1613 National Spec Single Material Response |

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/NAS1612-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.