

**Description**

Fastener Length: 25/32", Thread: 6-32, Thread Length: 19/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS16218
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-228-3977
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1621-8 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.251 Inches Minimum And 0.301 Inches Maximum
<b>Fastener Length:</b>	0.761 Inches Minimum And 0.791 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.231 Inches Minimum And 0.279 Inches Maximum
<b>Internal Drive Style:</b>	Torque Set
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740 Or Steel Comp 4037
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1621-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.