

**Description**

Fastener Length: 21/32", Thread: 6-32, Thread Length: 19/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                               |
|-------------------------|-------------------------------|
| SKU / Model:            | NAS1621E6                     |
| Minimum Qty (MOQ):      | 5 EA                          |
| NSN:                    | 5305-01-028-9178              |
| Schedule B:             | 7318.15.6080                  |
| ECCN:                   | 9A991                         |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE  
AVAILABLE

## P/N NAS1621E6 Specifications

|                                                             |                                                            |
|-------------------------------------------------------------|------------------------------------------------------------|
| <b>Thread Class:</b>                                        | 3a                                                         |
| <b>Thread Direction:</b>                                    | Right-hand                                                 |
| <b>Thread Length:</b>                                       | 0.251 Inches Minimum And 0.301 Inches Maximum              |
| <b>Fastener Length:</b>                                     | 0.636 Inches Minimum And 0.666 Inches Maximum              |
| <b>Head Style:</b>                                          | Flat Countersunk                                           |
| <b>Head Diameter:</b>                                       | 0.231 Inches Minimum And 0.279 Inches Maximum              |
| <b>Internal Drive Style:</b>                                | Torque Set                                                 |
| <b>Nominal Thread Diameter:</b>                             | 0.138 Inches                                               |
| <b>Thread Quantity Per Inch:</b>                            | 32                                                         |
| <b>Minimum Tensile Strength:</b>                            | 160000 Pounds Per Square Inch                              |
| <b>Countersink Angle:</b>                                   | 100.0 Degrees Nominal                                      |
| <b>Screw Material:</b>                                      | Iron Alloy 660                                             |
| <b>Screw Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response                 |
| <b>Screw Surface Treatment:</b>                             | Passivate                                                  |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response                 |
| <b>Thread Series Designator:</b>                            | Unjc                                                       |
| <b>Specification/standard Data:</b>                         | 80205-nas1621 Professional/Industrial Association Standard |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1621E6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.