

## **P/N NAS1622-2**

### **Description**

length: 0.401", thread: 8-32, flat head 100°, machine screw - offset cruciform - short thread

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS16222

Minimum Qty (MOQ): 50

NSN: 5305-00-959-2653

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1622-2 Specifications**

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.251 Inches Minimum And 0.301 Inches Maximum
Fastener Length:	0.386 Inches Minimum And 0.416 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.277 Inches Minimum And 0.334 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl @3 Fed Spec All Treatment Responses
Thread Series Designator:	Unc

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1622-2">https://military-fasteners.com/screws/machine+screws/NAS1622-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.