

Description

Fastener Length: 25/32", Thread: 8-32, Thread Length: 19/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS16228 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-458-4771 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1622-8 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.251 Inches Minimum And 0.301 Inches Maximum |
| Fastener Length: | 0.761 Inches Minimum And 0.791 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.277 Inches Minimum And 0.334 Inches Maximum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740 |
| Screw Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-8503 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-6049 Mil Spec 5th Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-b-416,ty 2,cl 3 Fed Spec All Treatment Responses |
| Thread Series Designator: | Unjc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1622-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.