

Description

NAS1630-2 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS16302
Minimum Qty (MOQ):	100
NSN:	5305-00-702-1613
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

P/N NAS1630-2 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.215 Inches Minimum And 0.225 Inches Maximum
Fastener Length:	0.330 Inches Minimum And 0.360 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 42.0 Rockwell C Maximum
Screw Material:	Steel Comp 430fse Or Steel Comp 81b45
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Q-p-416,ty 2,cl 3 Fed Spec 13th Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1630-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.