

**Description**

Fastener Length: 53/64", Thread: 1/4-28, Thread Length: 21/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | NAS16348                                  |
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5305-00-138-9818                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1634-8 Specifications

|                                                             |                                                                                                                                                                                                                               |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Thread Class:</b>                                        | 3a                                                                                                                                                                                                                            |
| <b>Thread Direction:</b>                                    | Right-hand                                                                                                                                                                                                                    |
| <b>Thread Length:</b>                                       | 0.291 Inches Minimum And 0.341 Inches Maximum                                                                                                                                                                                 |
| <b>Fastener Length:</b>                                     | 0.801 Inches Minimum And 0.831 Inches Maximum                                                                                                                                                                                 |
| <b>Head Style:</b>                                          | Pan                                                                                                                                                                                                                           |
| <b>Head Diameter:</b>                                       | 0.473 Inches Minimum And 0.492 Inches Maximum                                                                                                                                                                                 |
| <b>Head Height:</b>                                         | 0.162 Inches Minimum And 0.175 Inches Maximum                                                                                                                                                                                 |
| <b>Internal Drive Style:</b>                                | Torque Set                                                                                                                                                                                                                    |
| <b>Nominal Thread Diameter:</b>                             | 0.250 Inches                                                                                                                                                                                                                  |
| <b>Thread Quantity Per Inch:</b>                            | 28                                                                                                                                                                                                                            |
| <b>Minimum Tensile Strength:</b>                            | 160000 Pounds Per Square Inch                                                                                                                                                                                                 |
| <b>Hardness Rating:</b>                                     | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum                                                                                                                                                                           |
| <b>Screw Material:</b>                                      | Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740                                                                                                                                  |
| <b>Screw Material Document And Classification:</b>          | Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-8503 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-6049 Mil Spec 5th Material Response |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate                                                                                                                                                                                                          |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses                                                                                                                                                                           |
| <b>Thread Series Designator:</b>                            | Unjf                                                                                                                                                                                                                          |
| <b>Specification/standard Data:</b>                         | 80205-nas1634 Professional/Industrial Association Standard                                                                                                                                                                    |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1634-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.