

Description

Fastener Length: 5/8", Thread: 0-80, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS16350010
Minimum Qty (MOQ):	130 EA
NSN:	5305-00-728-1403
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1635-00-10 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.600 Inches Minimum
Fastener Length:	0.595 Inches Minimum And 0.625 Inches Maximum
Head Style:	Pan
Head Diameter:	0.104 Inches Minimum And 0.116 Inches Maximum
Head Height:	0.036 Inches Minimum And 0.044 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.060 Inches
Thread Quantity Per Inch:	80
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment:	Passivate And Chromate
Screw Surface Treatment Document And Classification:	Mil-c-13924 Mil Spec Single Treatment Response
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1635 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1635-00-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.