

**Description**

Fastener Length: 5/8", Thread: 0-80, Thread Length: 19/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS16350010
Minimum Qty (MOQ):	130 EA
NSN:	5305-00-728-1403
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1635-00-10 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.600 Inches Minimum
<b>Fastener Length:</b>	0.595 Inches Minimum And 0.625 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.104 Inches Minimum And 0.116 Inches Maximum
<b>Head Height:</b>	0.036 Inches Minimum And 0.044 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.060 Inches
<b>Thread Quantity Per Inch:</b>	80
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Screw Surface Treatment:</b>	Passivate And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Mil-c-13924 Mil Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	80205-nas1635 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1635-00-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.