

## P/N NAS1635-00-12

## **Description**

Fastener Length: 3/4", Thread: 0-80, Thread Length: 3/4

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS16350012

Minimum Qty (MOQ): 100

NSN: 5305-00-136-9897


Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







# P/N NAS1635-00-12 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.695 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.720 Inches Minimum And 0.750 Inches Maximum
Head Style:	Pan
Head Diameter:	0.104 Inches Minimum And 0.116 Inches Maximum
Head Height:	0.036 Inches Minimum And 0.044 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.060 Inches
Thread Quantity Per Inch:	80
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Mil-f-14072, finish E300 Mil Spec Single Treatment Response
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1635 Professional/industrial Association Standard

## **How to Order**

Order this close tolerance bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1635-00-12">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1635-00-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.