

Description

Fastener Length: 3/4", Thread: 0-80, Thread Length: 3/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS16350012 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-136-9897 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NAS1635-00-12



P/N NAS1635-00-12 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.695 Inches Minimum And 0.750 Inches Maximum |
| Fastener Length: | 0.720 Inches Minimum And 0.750 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.104 Inches Minimum And 0.116 Inches Maximum |
| Head Height: | 0.036 Inches Minimum And 0.044 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.060 Inches |
| Thread Quantity Per Inch: | 80 |
| Screw Material: | Steel Corrosion Resisting |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Mil-f-14072,finish E300 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas1635 Professional/industrial Association Standard |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1635-00-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.