

P/N NAS1635-00LE3

Description

Fastener Length: 3/16", Thread: 0-80, Thread Length: 3/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS163500LE3

Minimum Qty (MOQ): 20

NSN: 5305-00-431-7215


Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1635-00LE3 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.133 Inches Minimum And 0.188 Inches Maximum
Fastener Length:	0.158 Inches Minimum And 0.188 Inches Maximum
Head Style:	Pan
Head Diameter:	0.104 Inches Minimum And 0.116 Inches Maximum
Head Height:	0.036 Inches Minimum And 0.044 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.060 Inches
Thread Quantity Per Inch:	80
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-f-14072, finish E300 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1635 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-00LE3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.