

## P/N NAS1635-02-28

## **Description**

Fastener Length: 1-3/4", Thread: 2-56, Thread Length: 1-3/4

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS16350228
Minimum Qty (MOQ):	5
NSN:	5305-00-842-7509
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1635-02-28 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.714 Inches Minimum And 1.750 Inches Maximum
Fastener Length:	1.690 Inches Minimum And 1.750 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	35000 Pounds Per Square Inch
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Q-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

### **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-02-28">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-02-28</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.