

## P/N NAS1635-02LL7

### **Description**

Fastener Length: 7/16", Thread: 2-56, Thread Length: 7/16

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS163502LL7

Minimum Qty (MOQ): 15

NSN: 5305-00-395-4306

Schedule B: 7318.15.2091

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1635-02LL7 Specifications**

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.372 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.408 Inches Minimum And 0.438 Inches Maximum
Head Style:	Pan
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.053 Inches Minimum And 0.062 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-f-14072, finish E300 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1635 Professional/industrial Association Standard

## **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-02LL7">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-02LL7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.