

P/N NAS1635-04-28

Description

Fastener Length: 1-3/4", Thread: 4-40, Thread Length: 1-3/4", NAS1635 series screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS16350428

Minimum Qty (MOQ): 25

NSN: 5305-00-147-6167

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1635-04-28 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.640 Inches Minimum And 1.750 Inches Maximum
Fastener Length:	1.690 Inches Minimum And 1.750 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Mil-f-14072, finish E300 Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1635 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-04-28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.