

P/N NAS1635-06-10

Description

Length: 5/8", Thread: 6-32, Thread Length: 5/8", NAS1635 series screw

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS16350610

Minimum Qty (MOQ): 100

NSN: 5305-00-114-8859

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1635-06-10 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.563 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.595 Inches Minimum And 0.625 Inches Maximum
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1635 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-06-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.