

P/N NAS1635-06-9

Description

Fastener Length: 9/16", Thread: 6-32, Thread Length: 1/2", NAS1635 series screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | NAS1635069 |
|-------------------------|---|
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-00-935-3051 |
| Schedule B: | 7318.15.2091 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



^{*} See page 2 for technical characteristics

P/N NAS1635-06-9 Specifications

| Thread Class: | 2a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.470 Inches Minimum And 0.500 Inches Maximum |
| Fastener Length: | 0.532 Inches Minimum And 0.562 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.256 Inches Minimum And 0.270 Inches Maximum |
| Head Height: | 0.087 Inches Minimum And 0.097 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Screw Material: | Steel Corrosion Resisting |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |
| Specification/standard Data: | 80205-nas1635 Professional/industrial Association Standard |

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-06-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.