

Description

Fastener Length: 5/16", Thread: 6-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS163506LE5
Minimum Qty (MOQ):	5
NSN:	5305-00-321-9892
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1635-06LE5 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.220 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.282 Inches Minimum And 0.312 Inches Maximum
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Locking Feature:	Patch Or Pellet Or Strip
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Corrosion Resisting
Locking Feature Material:	Plastic Polyamide
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1635 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-06LE5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.