

Description

Fastener Length: 7/8", Thread: 8-32, Thread Length: 7/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS51957-48](#)

SKU / Model:	NAS16350814
Minimum Qty (MOQ):	100
NSN:	5305-01-029-8874
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1635-08-14 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.783 Inches Minimum And 0.875 Inches Maximum
Fastener Length:	0.845 Inches Minimum And 0.875 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Mil-f-14072,finish E300 Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1635 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-08-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.