

P/N NAS1635-08-34

Description

Fastener Length: 2-1/8", Thread: 8-32, Thread Length: 1-3/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS16350834	
Minimum Qty (MOQ):	15	
NSN:	5305-01-163-8235	
Schedule B:	7318.15.6080	

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1635-08-34 Specifications

Thread Class:	2a	
Thread Direction:	Right-hand	
Thread Length:	1.750 Inches Nominal	
Fastener Length:	2.035 Inches Minimum And 2.125 Inches Maximum	
Head Style:	Pan	
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum	
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum	
Internal Drive Style:	Cross Recess Type 1	
Nominal Thread Diameter:	0.164 Inches	
Thread Quantity Per Inch:	32	
Screw Material:	Steel Corrosion Resisting	
Screw Surface Treatment:	Passivate	
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response	
Thread Series Designator:	Unc	
Specification/standard Data:	80205-nas1635 Professional/industrial Association Standard	

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-08-34 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-08-34 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-08-34 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/nas164 and selecting the quantity you want then click "add to cart".