

Description

Fastener Length: 1/2", Thread: 8-32, Thread Length: 1/2", NAS1635 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS163508LE8 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-275-1934 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1635-08LE8 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.408 Inches Minimum And 0.500 Inches Maximum |
| Fastener Length: | 0.470 Inches Minimum And 0.500 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.306 Inches Minimum And 0.322 Inches Maximum |
| Head Height: | 0.105 Inches Minimum And 0.115 Inches Maximum |
| Locking Feature: | Strip Threads |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Material: | Steel Corrosion Resisting Fastener |
| Surface Treatment: | Passivate Fastener |
| Surface Treatment Document And Classification: | Mil-f-14072,e-300 Mil Spec Single Treatment Response Fastener |
| Thread Series Designator: | Unc |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-08LE8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.