

## P/N NAS1635-3-28

## **Description**

Fastener Length: 1-3/4", Thread: 10-32, Thread Length: 1-3/4", pan head

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS1635328
Minimum Qty (MOQ):	10
NSN:	5305-00-580-6239
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1635-3-28 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.628 Inches Minimum And 1.750 Inches Maximum
Fastener Length:	1.690 Inches Minimum And 1.750 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1635 Professional/industrial Association Standard

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1635-3-28">https://military-fasteners.com/screws/machine+screws/NAS1635-3-28</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.