

**Description**

Fastener Length: 7/16", Thread: 10-32, Thread Length: 7/16

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS16353LE7P
Minimum Qty (MOQ):	25
NSN:	5305-01-334-1454
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N NAS1635-3LE7P Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.346 Inches Minimum And 0.438 Inches Maximum
<b>Fastener Length:</b>	0.408 Inches Minimum And 0.438 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.357 Inches Minimum And 0.373 Inches Maximum
<b>Head Height:</b>	0.122 Inches Minimum And 0.133 Inches Maximum
<b>Locking Feature:</b>	Patch Or Pellet Or Strip
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Locking Feature Material:</b>	Plastic Polyamide
<b>Screw Surface Treatment:</b>	Oxide
<b>Color:</b>	Black
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	80205-nas1635 Professional/industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-3LE7P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.