

Description

Fastener Length: 1/2", Thread: 10-32, Thread Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS16353LN8
Minimum Qty (MOQ):	10
NSN:	5305-00-211-3436
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1635-3LN8 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.408 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.470 Inches Minimum And 0.500 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Locking Feature:	Pellet Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1635 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-3LN8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.