

Description

Fastener Length: 0-63/64", Thread: 3/8-24, Thread Length: 0-63/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1635616 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5305-01-137-8907 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1635-6-16 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.887 Inches Minimum And 1.000 Inches Maximum |
| Fastener Length: | 0.970 Inches Minimum And 1.000 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.716 Inches Minimum And 0.740 Inches Maximum |
| Head Height: | 0.244 Inches Minimum And 0.261 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.375 Inches |
| Thread Quantity Per Inch: | 24 |
| Screw Material: | Steel Corrosion Resisting |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas1635 Professional/industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1635-6-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.