

# P/N NAS1669-08DL6

Military-Fasteners.com

#### Description

grip range: 0.345" - 0.406", diameter: 0.164", general purpose, protruding head internally threaded, external sleeve with drive nut, NAS1669 series rivet

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | NAS166908DL6                                |
|-------------------------|---|
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5320-01-339-1948                            |
| Schedule B:             | 7318.15.2095                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



## P/N NAS1669-08DL6 Specifications

| Head Style:                                       | Hexagon  |
|---|--|
| Head Height:                                      | 0.096 Inches Maximum   |
| Shank Diameter:                                   | 0.1625 Inches Minimum And 0.1645 Inches Maximum  |
| Shank Style:                                      | Threaded Self-plugging Shank W/sleeve  |
| Expansion Device:                                 | Break Stem   |
| Grip Length:                                      | 0.345 Inches Minimum And 0.406 Inches Maximum  |
| Width Across Flats:                               | 0.244 Inches Minimum And 0.250 Inches Maximum  |
| Features Provided:                                | Drive Nut  |
| Special Features:                                 | Drive Nut Mild Steel Color Gold With Corrosion Retardent Coating   |
| Material:   | Steel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve  |
| Material:   | Steel Comp 4130 Bolt Or Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt   |
| Material:   | Steel Comp 4130 Nut Or Steel Comp 4140 Nut Or Steel Comp 8740 Nut  |
| Material Document And Classification:             | Astm A582 Assn Std 1st Material Response Sleeve Or Ams 5639 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std<br>3rd Material Response Sleeve |
| Material Document And Classification:             | Mil-s-6758 Mil Spec 1st Material Response Bolt Or Mil-s-5626 Mil Spec 2nd Material Response Bolt Or Mil-s-6049 Mil Spec 3rd<br>Material Response Bolt  |
| Material Document And Classification:             | Mil-s-6758 Mil Spec 1st Material Response Nut Or Mil-s-5626 Mil Spec 2nd Material Response Nut Or Mil-s-6049 Mil Spec 3rd<br>Material Response Nut     |
| Surface Treatment:                                | Cadmium Bolt And Chromate Bolt   |
| Surface Treatment:                                | Cadmium Nut And Chromate Nut   |
| Surface Treatment:                                | Passivate Sleeve And Cadmium Sleeve  |
| Surface Treatment Document And<br>Classification: | Qq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416,ty1,cl3 Fed Spec 2nd Treatment Response Sleeve   |
| Surface Treatment Document And<br>Classification: | Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Bolt   |
| Surface Treatment Document And<br>Classification: | Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Nut  |
| Specification/standard Data:                      | 80205-nas1669 Professional/industrial Association Standard   |
|   |  |

### How to Order

Order this blind rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/NAS1669-08DL6</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.