

Description

grip range: 0.094" - 0.156", diameter: 0.164", general purpose, protruding head internally threaded, external sleeve, NAS1669 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS166908L2
Minimum Qty (MOQ):	10
NSN:	5320-00-550-4792
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1669-08L2 Specifications

Fastener Length:	0.215 Inches Minimum And 0.245 Inches Maximum
Head Style:	Hexagon
Head Height:	0.096 Inches Nominal
Shank Diameter:	0.162 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Threaded Stem
Grip Length:	0.094 Inches Minimum And 0.156 Inches Maximum
Width Across Flats:	0.244 Inches Minimum And 0.250 Inches Maximum
Material:	Steel Body
Material:	Steel Corrosion Resisting Sleeve
Material:	Steel Stem
Surface Treatment:	Cadmium Overall
Specification/standard Data:	80205-nas1669 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1669-08L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.